

Mounting instruction

Brochure holder system

Uncut wires

IS-9310	Wire system with 4 meter (157.5") wires
Pre-cut wires	
IS-9311	Wire system <i>for Midi</i> 2470 mm (97.2") panels
IS-9312	Wire system for Maxi 2270 mm (89.4") panels

IS-9318 Brochure holders A4 / US letter with 4 connectors

Please observe: This system can only be used with a straight Compact or Straight graphic wing module





Mounting instruction



Push in the small H-profile at the top of the beam and then mount the extra beam in top of that profile.



2 Mount this assembly at to top of the posts.



3 Attach the graphic panel and adjust the base beam so that its bottom edge aligns exactly with the bottom edge of the graphic.



4 Hook the top connector of the wire assembly to the top beam.





5 Mount the first bottom connector.



6 Screw the bottom fitting of the wire assembly into the connector until the wire is tight. Repeat the process with the top fitting.



7 Attach the four indentical grip connectors to the brochure holder, evenly spaced. Do not overtighten.



8 Remove the side screws in the grip connectors, position the wire inside the grooves, and resintall the side screws.



9 You can now attach more brochure pockets.



Mark Bric Display Corp. North America Tel. 800.742.6275 Fax 800.565.9506 E-mail: markbric@markbric.com



Mark Bric Display AB Worldwide Headquarters Tel. +46 33 480 460 Fax +46 33 480 470 E-mail: display@markbric.se



Cuting wire

Brochure holder system

Uncut wires IS-9310 Wire system with 4 meter (157.5") wires Pre-cut wires Wire system *for Midi* 2470 mm (97.2") panels Wire system *for Maxi* 2270 mm (89.4") panels IS-9311 IS-9312

Brochure holders A4 / US letter with 4 connectors IS-9318

Cutting wire length

Panel height 2270 mm (89.4") 2470 mm (97.2") 4000 mm (157.5")

Wire length 2230 mm (87.8") 2430 mm (95.6") 3960 mm (155.9"



Only for uncut wires Adjust the bottom lock bracket and cut the wire to the desired length.



